



Features

- True-flat, bezel-free, fanless design
- 16:9 widescreen 15.6in LCD (1366x768)
- High performance Intel Quad-Core processor
- Durable and sturdy base
- Easy to change or replace hard disk drive
- Optional MSR and VFD/LCD customer display

SB1015W

True-flat 15.6in Touch Screen POS Terminal

The SB1015W is a cost effective 15.6in true-flat touch screen All-in-One Point-of-Sale terminal. The terminal packs great features and value into a sleek and sturdy design. It delivers an economical POS solution while providing excellent performance and reliability. The highly rugged touch monitor includes a solid base with extra wide hinge for maximum stability. The SB1015W also facilitates options for quick and professional mounting of integrated magnetic stripe reader and VFD/LCD customer display.



bematechus.com



SB1015W SPECIFICATIONS

ELECTRICAL

Power supply	External power adapter, DC 12V 80W min.
Input to power adapter	100 to 240VAC, 50/60Hz

MAINBOARD

CPU	Intel Celeron J1900 Quad-Core 2.0GHz
IO chipset	Intel IT 8718F-S
Memory	DDR3L 1333 1.35V SODIMM slot, up to 8GB
Ethernet LAN	Realtek RTL8111F PCI Express Gigabit LAN
Audio	ALC887 Audio CODEC, HD Audio CODEC
Storage	SATA 2.5in Hard Disk Drive/SSD, mSATA SSD



DISPLAY

Touch screen	5 wire resistive touch, optional projected capacitive touch
Touch controller	USB interface
LCD panel	15.6in TFT display, WXGA 1366 x 768, 200 nits

I/O PORTS

USB ports	USB2.0 x4, USB3.0 x2
Serial ports	RS232 DB9 x2
Ethernet	Gigabit, RJ45 x1
Video port	VGA DB15 x1
Audio port	Line out x1



ENVIRONMENTAL

Operating temperature	32°F to 104°F (0°C to 40°C)
Relative humidity	8% to 80%, non-condensing

MECHANICAL

Dimensions (W x H x D)	15.9in x 12.1in x 9.0in (40.6cm x 30.8cm x 23.0cm)
Weight	13lbs (5.91Kg)

OPTIONAL PERIPHERALS

Customer Display	VFD 20 columns x 2 lines (USB) or 8in true-flat LCD (VESA holes 75x75, USB)
MSR	JIS-I or II, ISO Track 1/2/3 (USB)

*Images shown with available customer display and MSR options