

TP585L

2-inch Thermal Receipt Printer

Product Features

- Cubic shape, small footprint
- Paper feeding, save space for countertop
- USB, Serial for connection, Bluetooth is optional



Alternative
dual-mode Bluetooth 4.0



Paper saving mode



Error reprint function

Specification

Model		TP585L
Print Parameter	Print Method	Direct thermal line printing
	Resolution	203 dpi
	Print Speed	Max. 100 mm/s
	Print Width	48 mm
	Command	ESC/POS
	Page Mode	No
	Paper feeding	Front paper feeding
Paper	Paper Type	Thermal receipt paper
	Paper Width	58 mm
	Paper Thickness	0.05~0.08 mm
	Roll paper Diameter	Max. 60 mm
Character and Barcode	Character Specification	Simplified Chinese/traditional Chinese/Korean/Japanese, 47 codepage
Detection	Sensor	Paper end sensor, cover opening sensor, over-temperature sensor, over-voltage sensor
Barcode Printing	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code, PDF417
Memory	RAM	256 KB
	Flash	4 MB
Cut Method		Tear bar
Reliability	TPH Life	100 KM
Interface	Default	USB, Serial
	Optional	Dual-mode Bluetooth
Electrical Parameter	Input	AC100~240V, 50~60Hz
	Output	DC 12V, 2A
Environmental Parameter	Operating	0~40°C, 20~85%RH, non-condensing
	Storage	-20~60°C, 5~95%RH, non-condensing
Physical Parameter	Dimension(L*W*H)	110*105*114(mm)

Application



Xiamen Hanin Electronic Technology Co.,Ltd.

Address: 1-5F, NO.8, Gaoqi South 12 th Road,Xiamen, China
 Telephone: + 86-(0)592 -5885993
 E-mail: overseas@hpert.com
 Website: www.hpert.com

Brochure Version: 202204



HPRT Official Website